



## SPECIFICATIONS

	Insignia5	Insignia6	Insignia7	InsigniaX <sup>3</sup>
Material Thickness	Minimum: 60lb Cover / 50gsm <b>Maximum: 0.024" / 400gsm</b>	Minimum: 60lb Cover / 50gsm <b>Maximum: 0.024" / 400gsm</b>	Minimum: 60lb Cover / 50gsm <b>Maximum: 0.024" / 400gsm</b>	Minimum: 60lb Cover / 50gsm <b>Maximum: 0.030" / 550gsm</b>
Sheet Size	8x8" Minimum (20x20cm) <b>20x15" Maximum (51x38cm)</b>	8x8" Minimum (20x20cm) <b>20x20" Maximum (51x51cm)</b>	8x8" Minimum (20x20cm) <b>30x24" Maximum (76x61cm)</b>	8x8" Minimum (20x20cm) <b>24x24" Maximum (61x61cm)</b>
Speed	Variable up to 5,000 sheets per hour	Variable up to 5,000 sheets per hour	Variable up to 5,000 sheets per hour	Variable up to 5,000 sheets per hour
Register	4 Adjustable front head stops Side guide; pull left or right Gripper finger cam system	4 Adjustable front head stops Side guide; pull left or right Gripper finger cam system	8 Adjustable front head stops Side guide; pull left or right Gripper finger cam system	6 Adjustable front head stops Side guide; pull left or right Gripper finger cam system
Feed	Top suction air feed w/ 3 movable sucker heads. Front & side air separation. Feed capacity of ~36"	Top suction air feed w/ 3 movable sucker heads. Front & side air separation. Feed capacity of ~36"	Top suction air feed w/ 4 movable sucker heads. Front & side air separation. Feed capacity of ~40"	Top suction air feed w/ 4 movable sucker heads. Front & side air separation. Feed capacity of ~36"
Cylinder Options	Upper: magnetic, ceramic & steel Lower: Hard anvil no lower jacket required	Upper: magnetic, ceramic & steel Lower: Hard anvil, no jacket required <b>Optional dual magnetic system</b>	Upper: magnetic, ceramic & steel Lower: Hard anvil, no jacket required <b>Optional dual magnetic system</b>	Upper: magnetic, ceramic & steel Lower: Hard anvil no lower jacket required
Air Supply	Becker feed pump built in. Compressed house air or air compressor required for stripping unit air knives.	Becker feed pump built in. Compressed house air or air compressor required for stripping unit air knives.	Becker feed pump built in. Compressed house air or air compressor required for stripping unit air knives.	Becker feed pump built in. Compressed house air or air compressor required for stripping unit air knives.
Electrical Rqt.	230v - 60Hz - 3-phase - 12amp 110v 1-phase line *Other voltages available	230v - 60Hz - 3-phase - 12amp 110v 1-phase line *Other voltages available	230v - 60Hz - 3-phase - 15amp 110v 1-phase line *Other voltages available	230v - 60Hz - 3-phase - 15amp 110v 1-phase line *Other voltages available
Footprint (die cutter only)	60" long X 48" tall X 40" wide 152cm long X 122cm tall X 101cm wide	68" long X 51" tall X 40" wide 172cm long X 129cm tall X 101cm wide	79" long X 58" tall X 55" wide 200cm long X 147cm tall X 140cm wide	79" long X 58" tall X 49" wide 200cm long X 147cm tall X 125cm wide
Weight (die cutter only)	2,900lbs 1,315kgs	3,600lbs 1,630kgs	4,800lbs 2,200kgs	4,200lbs 1,905kgs